

KARMA

WEIGHT AND DIMENSIONS

TABELLA MISURE E PESI | TABLEAU DES POIDS ET DIMENSIONS |  
GRÖÖBE UND GEWICHTE | TABLA DE MEDIDAS Y PESOS | РАЗМЕРЫ И ВЕС

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |                                                                                                                |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------|
| SIZE<br>FORMATO<br>FORMAT<br>FORMAT<br>TAMAÑO<br>РАЗМЕР                                                                                                                                                                                                                                                                                                                                                                                                                         | SHEETS SIZE<br>DIMENSIONE FOGLI<br>DIMENSION PLAQUES<br>ABMESSUNG DER BLÄTTER<br>MEDIDAS HOJAS<br>РАЗМЕР ЛИСТА |
| 2 x 2 cm   3/4" x 3/4"                                                                                                                                                                                                                                                                                                                                                                                                                                                          | 31,6 x 31,6 cm<br>12 7/16" x 12 7/16"                                                                          |
| 4 x 4 cm   1 1/2" x 1 1/2"                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 29,3 x 29,3 cm<br>11 1/2" x 11 1/2"                                                                            |
| 2 x 4 cm   3/4" x 1 1/2"<br>Aligned joint   Giunto allineato   Joint aligné  <br>Gerade geklebt   Junta alineada   Шов прямой                                                                                                                                                                                                                                                                                                                                                   | 29,3 x 31,6 cm<br>11 1/2" x 12 7/16"                                                                           |
| 2 x 4 cm   3/4" x 1 1/2"<br>Staggered joint   Giunto sfalsato   Joint décalé<br>Versetzt geklebt   Junta partida   Шов смещенный                                                                                                                                                                                                                                                                                                                                                | 29,3 x 29,5 cm<br>11 1/2" x 11 5/8"                                                                            |
| 4 x 8 cm   1 1/2" x 3"<br>Aligned joint   Giunto allineato   Joint aligné  <br>Gerade geklebt   Junta alineada   Шов прямой                                                                                                                                                                                                                                                                                                                                                     | 25,1 x 29,3 cm<br>9 7/8" x 11 1/2"                                                                             |
| THICKNESS<br>SPESSORE<br>EPAISSEUR<br>STÄRKE<br>ESPESOR<br>ТОЛЩИНА                                                                                                                                                                                                                                                                                                                                                                                                              | ~ 4 mm   5/32"                                                                                                 |
| JOINT<br>GIUNTO<br>JOINT<br>ABMESSUNG DER FUGE<br>JUNTA<br>ШОВ                                                                                                                                                                                                                                                                                                                                                                                                                  | ~ 1 mm   1/16"                                                                                                 |
| WEIGHT<br>PESO<br>POIDS<br>GEWICHT<br>PESO<br>BEC                                                                                                                                                                                                                                                                                                                                                                                                                               | ~10 kg/m²   2 lbs/SQF                                                                                          |
| Hand cut   Tagliato a mano   Coupé à la main   Handgeschnitten<br>Cortado a mano   наколотые вручную                                                                                                                                                                                                                                                                                                                                                                            |                                                                                                                |
| Data are indicative only as it is a hand-cut product.<br>I dati sono indicativi dal momento che si tratta di un prodotto artigianale.<br>Comme il s'agit d'un produit artisanal, ces données n'ont qu'une valeur<br>indicative.<br>Da es sich um handwerkliche Produkte handelt, sind die obenerwähnten<br>Angaben als Richtwerte zu betrachten.<br>Los datos son indicativos por tratarse de un producto artesanal.<br>Материал ручной работы, поэтому данные приблизительные. |                                                                                                                |

**FOR THE APPLICATION IN HUMID ZONES, TREND SUGGESTS USING EPOXY ADHESIVES AND GROUTS. FOR FURTHER INFORMATION PLEASE CONTACT TREND GROUP.**

NEL CASO DI INSTALLAZIONE IN AMBIENTI UMIDI TREND CONSIGLIA DI UTILIZZARE ADESIVI E FUGANTI EPOSSIDICI. PER ULTERIORI INFORMAZIONI CONTATTARE TREND GROUP S.P.A.

EN CAS D'INSTALLATION DANS DES LIEUX HUMIDES, TREND SUGGÈRE L'UTILISATION DES ADHÉSIFS ET JOITS ÉPOXY. POUR D'ULTÉRIEURES INFORMATIONS VEUILLEZ CONTACTER TREND GROUP.

IM NASSBEREICH EMPFEHLT TREND KLEBER UND FUGENMASSE AUF EPOXYBASIS. FÜR WEITERE FRAGEN NEHMEN SIE BITTE MIT IHREM ANSPRECHPARTNER BEI DER FA. TREND GROUP KONTAKT.

PARA LA COLOCACIÓN EN AMBIENTES HÚMEDOS UTILIZAR ADHESIVOS Y MATERIAL DE REJUNTADO EPÓXICOS. PARA AMPLIAR LA INFORMACIÓN CONTACTAR CON TREND GROUP.

В СЛУЧАЕ УКЛАДКИ В МЕСТАХ, СОДЕРЖАЩИХ ВЛАГУ, TREND РЕКОМЕНДУЕТ ИСПОЛЬЗОВАТЬ ЭПОКСИДНЫЙ КЛЕЙ И ЗАТИРКУ. ЗА ДОПОЛНИТЕЛЬНОЙ ИНФОРМАЦИЕЙ ОБРАЩАЙТЕСЬ В TREND GROUP.

TEST DATA

CARATTERISTICHE TECNICHE | CARACTÉRISTIQUES TECHNIQUES |  
TECHNISCHE EIGENSCHAFTEN | CARACTERÍSTICAS TÉCNICAS |  
ТЕХНИЧЕСКИЙ РАЗДЕЛ

|                                                                                                                                                                                                                         |                                                                              |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------|
|                                                                                                                                        | UNI EN ISO 10545 (13)                                                        |
| RESISTANCE TO CHEMICAL AGENTS<br>RESISTENZA AGLI AGENTI CHIMICI<br>RESISTANCE AUX PRODUITS CHIMIQUES<br>SÄURE- UND LAUGENBESTÄNDIGKEIT<br>RESISTENCIA A LOS AGENTES QUÍMICOS<br>УСТОЙЧИВОСТЬ К ВОЗДЕЙСТВИЮ КИСЛОТ       | resistant<br>resistente<br>résistant<br>beständig<br>resistente<br>устойчива |
|                                                                                                                                        | UNI EN ISO 10545 (9)                                                         |
| RESISTANCE TO THERMAL SHOCKS<br>RESISTENZA AGLI SBALZI TERMICI<br>RESISTANCE AUX CHOCS THERMIQUES<br>TEMPERATURWECHSELBESTÄNDIGKEIT<br>RESISTENCIA A LOS CAMBIOS DE TEMPERATURA<br>УСТОЙЧИВОСТЬ К ПЕРЕПАДАМ ТЕМПЕРАТУРЫ | resistant<br>resistente<br>résistant<br>beständig<br>resistente<br>устойчива |
|                                                                                                                                        | UNI EN ISO 10545 (3)                                                         |
| WATER ABSORPTION<br>ASSORBIMENTO ACQUA<br>ABSORPTION D'EAU<br>WASSERAUFNAHME<br>ABSORCION DE AGUA<br>ВОДОПОГЛОЩЕНИЕ                                                                                                     | none<br>nullo<br>nulle<br>null<br>nula<br>ноль                               |
|                                                                                                                                      | DIN 51094                                                                    |
| COLORS RESISTANCE TO FADING<br>RESISTENZA DEI COLORI ALLA LUCE<br>RESISTANCE DES COULEURS A LA LUMIERE<br>FARBBESTÄNDIGKEIT<br>RESISTENCIA DE LOS COLORES A LA LUZ<br>УСТОЙЧИВОСТЬ К СВЕТУ                              | resistant<br>resistente<br>résistant<br>beständig<br>resistente<br>устойчива |
|                                                                                                                                      | UNI EN ISO 10545 (12)                                                        |
| FROST RESISTANCE<br>RESISTENZA AL GELO<br>RESISTANCE AU GEL<br>FROSTBESTÄNDIGKEIT<br>RESISTENCIA AL HIELO<br>МОРОЗОУСТОЙЧИВОСТЬ                                                                                         | resistant<br>resistente<br>résistant<br>beständig<br>resistente<br>устойчива |

TEST ASTM

| TEST PERFORMED AND REQUIREMENTS | CONCLUSIONS |
|---------------------------------|-------------|
| Range of thickness (ASTM C499)  | passes      |
| Facial dimensions (ASTM C499)   | passes      |
| Wedging (ASTM C502)             | passes      |
| Water absorption (ASTM C373)    | passes      |
| Thermal shocks (ASTM C484)      | passes      |
| Bond Strenght (ASTM C482)       | passes      |
| Crazing (ASTM C424)             | passes      |