REGIO
WEIGHT AND DIMENSIONS
TABELLA MISURE E PESI | TABLEAU DES POIDS ET DIMENSIONS | GRÖßE UND GEWICHTE | TABLA DE MEDIDAS Y PESOS | РАЗМЕРЫ И ВЕС

MODULAR SIZE FORMATO MODULO FORMAT MODULE MODULGRÖSSE FORMATO MÓDULO Формат м одуля	26,4 x 26,4 cm 10 3/8" x 10 3/8"
THICKNESS SPESSORE EPAISSEUR STÄRKE ESPESOR ТОЛЩИНА	~ 4 mm | 5/32"
JOINT GIUNTO JOINT ABMESSUNG DER FUGE JUNTA ШОВ	~ 1 mm | 1/16"
WEIGHT PESO POIDS GEWICHT PESO ВЕС	~10 kg/m^2 | 1.6 lbs/SQF

Hand cut | Tagliato a mano | Coupé à la main | Handgeschnitten
Cortado a mano | наколотые вручную

Data are indicative only as it is a hand-cut product.
I dati sono indicativi dal momento che si tratta di un prodotto artigianale.
Comme il s'agit d'un produit artisanal, ces données n'ont qu'une valeur indicative.
Da es sich um handwerkliche Produkte handelt, sind die obenerwähnten Angaben als Richtwerte zu betrachten.
Los datos son indicativos por tratarse de un producto artesanal.
Материал ручной работы, поэтому данные приблизительные.

FOR THE APPLICATION IN HUMID ZONES, TREND SUGGESTS USING EPOXY ADHESIVES AND GROUTS. FOR FURTHER INFORMATION PLEASE CONTACT TREND GROUP.

NEL CASO DI INSTALLAZIONE IN AMBIENTI UMIDI TREND CONSIGLIA DI UTILIZZARE ADESIVI E FUGANTI EPOSSIDICI. PER ULTERIORI INFORMAZIONI CONTATTARE TREND GROUP S.P.A.

EN CAS D'INSTALLATION DANS DES LIEUX HUMIDES, TREND SUGGÈRE L'UTILISATION DES ADHÉSIFS ET JOITS ÉPOXY. POUR D'ULTÉRIEURES INFORMATIONS VEUILLEZ CONTACTER TREND GROUP.

IM NASSBEREICH EMPFEHLT TREND KLEBER UND FUGENMASSE AUF EPOXYBASIS. FÜR WEITERE FRAGEN NEHMEN SIE BITTE MIT IHREM ANSPRECHPARTNER BEI DER FA. TREND GROUP KONTAKT.

PARA LA COLOCACIÓN EN AMBIENTES HÚMEDOS UTILIZAR ADHESIVOS Y MATERIAL DE REJUNTADO EPÓXICOS. PARA AMPLIAR LA INFORMACIÓN CONTACTAR CON TREND GROUP.

В СЛУЧАЕ УКЛАДКИ В МЕСТАХ, СОДЕРЖАЩИХ ВЛАГУ, TREND РЕКОМЕНДУЕТ ИСПОЛЬЗОВАТЬ ЭПОКСИДНЫЙ КЛЕЙ И ЗАТИРКУ. ЗА ДОПОЛНИТЕЛЬНОЙ ИНФОРМАЦИЕЙ ОБРАЩАЙТЕСЬ В TREND GROUP.

TEST DATA
CARATTERISTICHE TECNICHE | CARACTÉRISTIQUES TECHNIQUES | TECHNISCHE EIGENSCHAFTEN | CARACTERÍSTICAS TÉCNICAS | ТЕХНИЧЕСКИЙ РАЗДЕЛ

UNI EN ISO 10545 (13)	
RESISTANCE TO CHEMICAL AGENTS	resistant
RESISTENZA AGLI AGENTI CHIMICI	resistente
RESISTANCE AUX PRODUITS CHIMIQUES	résistant
SÄURE- UND LAUGENBESTÄNDIGKEIT	beständig
RESISTENCIA A LOS AGENTES QUÍMICOS	resistente
УСТОЙЧИВОСТЬ К ВОЗДЕЙСТВИЮ КИСЛОТ	устойчива

UNI EN ISO 10545 (9)	
RESISTANCE TO THERMAL SHOCKS	resistant
RESISTENZA AGLI SBALZI TERMICI	resistente
RESISTANCE AUX CHOCS THERMIQUES	résistant
TEMPERATURWECHSELBESTÄNDIGKEIT	beständig
RESISTENCIA A LOS CAMBIOS DE TEMPERATURA	resistente
УСТОЙЧИВОСТЬ К ПЕРЕПАДАМ ТЕМПЕРАТУРЫ	устойчива

UNI EN ISO 10545 (3)	
WATER ABSORPTION	none
ASSORBIMENTO ACQUA	nullo
ABSORPTION D'EAU	nulle
WASSERAUFNAHME	null
ABSORCION DE AGUA	nula
ВОДОПОГЛОЩЕНИЕ	ноль

DIN 51094	
COLORS RESISTANCE TO FADING	resistant
RESISTENZA DEI COLORI ALLA LUCE	resistente
RESISTANCE DES COULEURS A LA LUMIERE	résistant
FARBBESTÄNDIGKEIT	beständig
RESISTENCIA DE LOS COLORES A LA LUZ	resistente
УСТОЙЧИВОСТЬ К СВЕТУ	устойчива

UNI EN ISO 10545 (12)	
FROST RESISTANCE	resistant
RESISTENZA AL GELO	resistente
RESISTANCE AU GEL	résistant
FROSTBESTÄNDIGKEIT	beständig
RESISTENCIA AL HIELO	resistente
МОРОЗОУСТОЙЧИВОСТЬ	устойчива

TEST ASTM

TEST PERFORMED AND REQUIREMENTS	CONCLUSIONS
Range of thickness (ASTM C499)	passes
Facial dimensions (ASTM C499)	passes
Wedging (ASTM C502)	passes
Water absorption (ASTM C373)	passes
Thermal shocks (ASTM C484)	passes
Bond Strenght (ASTM C482)	passes
Crazing (ASTM C424)	passes